

Fixed dome 4 in 1 HYUNDAI NEXT GEN PRO series

FEATURES

- Fixed dome 4 in 1 HYUNDAI NEXT GEN PRO series
- Smart IR up to 40 meters
- 2 megapixel CMOS
- 1080P (1920x1080) resolution at 25 ips
- 2.8 mm (106.4 °) fixed lens
- Switchable 4-in-1 video output
- ICR filter
- OSD menu control via coaxial cable (UTC)
- Digital WDR, 2D-DNR
- It incorporates a microphone
- Supports coaxial cable audio transmission (only compatible with ZVR HYUNDAI with audio)
- Metal and plastic housing
- Degree of protection IP67
- 3AXIS
- 12V DC



SPECS

- 5-in-1 4-channel ZVR format H.265 Pro + / H265 Pro / H.265 / H.264 + / H.264
- 5 technologies: IP cameras, HDCVI, HDTVI, AHD and analog CVBS
- H.265 Pro + / H.265 Pro can be enabled to improve coding efficiency and reduce data storage costs
- 8 BNC inputs (supports coaxitron):
- HDCVI: 4MP / 1080P / 720P at 25 fps
- HDTVI: 8MP / 5MP / 4MP / 3MP / 1080P at 25 fps, 720P at 25/50 fps
- AHD: 5MP / 4MP / 1080P / 720P at 25 fps
- Analog CVBS: 960H
- 12 IP inputs up to 8MP (8 + 4)
- Possibility of obtaining 16 IP inputs (8 + 8) at 4Mbps, activating the enhanced IP mode
- Simultaneous VGA (1080P) and HDMI (2K, 4K) outputs
- BNC video output
- 1 RCA input / 1 RCA output
- Bidirectional audio
- Supports coaxial cable audio (only compatible with HYUNDAI NEXTGEN cameras with coaxial audio)
- Recording resolution: 8MP (TVI / IP only), 5MP, 4MP, 3MP, 1080P, 720P, WD1, 4CIF, VGA, CIF
- Stream 1: 8MP (8 fps), 5MP (12 fps), 4MP (15 fps), 3MP (18 fps), 1080P / 720P / WD1 / 4CIF / VGA / CIF (25 fps)
- Stream 2: WD1 / 4CIF / CIF (25 fps)
- 8-channel synchronized playback
- Internal capacity for 1 SATA HDD up to 10TB (sold separately)
- Graphical user interface (GUI) and support one-key recording start (Wizard)
- Smart search for more efficient playback
- Supports third-party cloud storage (Dropbox, Google Drive, Microsoft OneDrive)
- Up to 4 channels of deep analysis based on learning: recognition of people or vehicles in the detection
- of behaviors to reduce false alarms
- Up to 1 face detection channel
- RJ45 (10/100 / 1000M) Ethernet network interface auto-adaptive
- Network protocols: TCP / IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
- ONVIF compatible
- Remote access for up to 64 users
- Remote access through iPhone / iPad devices, Android
- Multi browser compatibility: Chrome, Firefox, Safari, IE
- P2P in the cloud, DDNS DEMES, Push and zero channel
- Connections: 1 USB 2.0, 1 USB 3.0, 1 RS485 half-duplex
- Power: 12V DC
- Consumption: ≤15W
- Working temperature: -10 ° C ~ + 55 ° C
- RH: 10 ~ 90%
- Dimensions: 315 x 242 x 45 mm (desktop)
- Weight: ≤1.16 kg