

# HYU-771

SF-IPB786ZH-2E

HYUNDAI

## HYUNDAI NEXT GEN Performance Line IP vandal bullet camera with IR of 30m, 2 MP for outdoors

HYUNDAI  PerformanceLine   ONVIF 

- HYUNDAI NEXT GEN Performance Line IP vandal bullet camera with IR of 30m, 2 MP for outdoors
- H.265 / H.264 / MJPEG format
- 1/2.8" CMOS, 2MP
- Digital resolution 1080P @ 25FPS
- Mechanical filter
- 0.028 lux
- 2.8 ~ 12 mm motor lens (99.6 ° ~ 35 °)
- OSD, AGC, BLC, WDR 120dB , 3D-DNR, motion detection, privacy masks, fixed ROI zone, intelligent analysis, 3AXIS, 12V DC, PoE.



### Reference / Model

HYU-771 / SF-IPB786ZH-2E

1/2.8" CMOS sensor, 2 MP

Up to 1080P (1920x1080) at 25 fps

2.8 ~ 12mm motor lens with autofocus

H.265 +, H.265, H.264 +, H.264 video compression

Dual stream

WDR 120dB, BLC, 3D-DNR, 1 ROI

Analysis of up to 2 behaviors

IR of 30 meters

MicroSD card slot up to 128GB (card not included)

IP67

PoE supported

### Specs

1/2.8" CMOS sensor, 2 MP

**HYUNDAI NEXT GEN Performance Line IP vandal bullet camera with IR of 30m, 2 MP for outdoors**

<b>Reference / Model</b>	<b>HYU-771 / SF-IPB786ZH-2E</b>
Digital resolution: 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), etc.	
Compression format H.265+ / H.265 / H.264+ / H.264 / MJPEG	
Main Stream: 1080P, 1.3MP, 720P (25 fps)	
Secondary stream: 640x480, 640x360, 320x240 (25 fps)	
Day / night mode with removable mechanical filter	
IR: 30 meters	
0.028 lux F2.0 color / 0 lux IR On	
2.8 ~ 12mm motor lens with autofocus	
Viewing angle: 99.6 ° ~ 35 ° (H), 53.5 ° ~ 20 ° (V), 118.6 ° ~ 40.2 ° (D)	
OSD menu	
Automatic gain control	
Backlight Compensation: BLC	
WDR 120dB	
3D digital noise reduction	
1 fixed ROI zone main stream	
Motion detection and privacy mask	
Adjust brightness, saturation, contrast, sharpness, image rotation adjustable using client software or web browser	
Intelligent analysis: Line crossing detection, intrusion detection	
MicroSD card slot up to 128GB (card not included)	
Reset button	
Network interface: RJ45 (10 / 100M) auto-adaptive	
Network protocols: TCP / IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour	
Compatible with ONVIF (Profile S, G), ISAPI	
Plug & Play connection with NVR NEXTGEN	
DDNS DEMES compatible	

**HYUNDAI NEXT GEN Performance Line IP vandal bullet camera with IR of 30m, 2 MP for outdoors**

<b>Reference / Model</b>	<b>HYU-771 / SF-IPB786ZH-2E</b>
	Compatible with IE8 +, Chrome 31-44, Firefox30-51, Safari 8+ browsers
	Power supply: 12V DC (± 25%)
	Consumption: 11W (PoE 12.9W)
	Supports 802.3af PoE, class 3
	Working temperature: -30 ° C ~ + 50 ° C
	Humidity: 95% (without condensation)
	IP67
	Metalcase
	Dimensions: Ø105 x 294.5 mm
	Weight: 1.05 kg
	3AXIS: 0 ° ~ 360 ° (PAN), 0 ° ~ 100 ° (TILT), 0 ° ~ 360 ° (ROTATION)
	Power supply is not included